

**POWER PACK 15 VDC @ 1 AMP
(17-2004-03)**

Accu-Time's PN 17-2004-03 is a fifteen (15) volt DC (Direct Current) power source which provides the necessary voltage level to power up Accu-Time Data Collection Terminals (DCT), auxiliary peripheral devices and communication converters.

The primary or input to this power pack accommodates a 60 Hertz 120 volt AC (Alternating Current) line level. The pack delivers an unregulated output, or secondary level, of 15 volts DC at 1 ampere of current.

The Accu-Time 15VDC power pack is an approved Class 2 Transformer assembly listed by both Underwriters Laboratory (UL), and Canadian Standards Association (CSA).

Housed in a high impact sealed plastic casing, the Accu-Time 15VDC @ 1 amp power pack comes equipped with a six- (6) foot output cord and 2.5mm inner-diameter termination plug (5.5mm outer diameter). This female barrel plug is center conductor positive and mates to the entire Accu-Time product line.

GENERAL SPECIFICATIONS

Physical-

Dimensions: 3.52"L X 2.42"W X 1.87"H
(8.94cmL x 6.15cmW x 4.75cmH)
Weight: 1.3 LBS (0.59 kg.)

Enclosure: Black Noryl®, UL94V-0

Environmental-

Operating Temp: 32° to 110° F (0°to 45°C)

Relative Humidity: 20-90% Non Condensing

Operating Parameters-

Power: Primary 120VAC 60Hz 24W
Secondary 15VDC +- 5% @ 1 amp

