

## HAND-HELD CCD BARCODE SCANNER 9000/39

Accu-Time P/N 9000/39 is a barcode scanner with a comfortable pistol-grip design that can be either hand-held or mounted on the supplied flexible stand for hands-free operation. It features a long-range CCD scan engine, extra depth of field, and a scanning width of up to 7 inches (18cm). An adjustable audio beeper and clearly visible "good read" LED provide positive feedback to the user.

The unit can be connected using the supplied cable to any Accu-Time terminal that accepts wand input. Supported codes include Code 3 of 9, Code 128, Codabar, Code I 2 of 5, and UPCA.

### Specifications:

Light source: 660 nm red LED

Sensor: 3000 element linear array

Depth of field Resolution - Symbology @ Reading Distance

4mil - Code 39 @ 65 to 70mm

5mil - Code 39 @ 65 to 90mm

10mil - Code 39 @ 55 to 140mm

Scan rate: 50 scans/second

Scanning area: 7.08" (180mm) maximum

Print contrast ratio: 45% minimum absolute dark/light reflectance @ 660 nm

Operation modes: Trigger, flash, or continuous

Dimensions: 7.1 Inches (180mm) x 2.75 Inches (70mm) x 3.9 Inches (100mm)

Weight: 5.8 oz. (164g)

Operating voltage: 5V  $\pm$ 5%

Operating current: 175 mA

Idle current: 80 mA

Operating temperature: 32°F to 122°F  
(0°C to 50°C)

Storage temperature: -4°F to 140°F  
(-20°C to 60°C)

Humidity: 20% to 85% RH non-condensing

Mechanical shock: 5 feet (1.5 meters) drop onto  
concrete

ESD protection: Contact: 8K, Air: 12K

Regulatory approvals: CE, FCC, BSMI



9000/39